










soft top jaws

steel ■ aluminium

METRIC serration
1,5 x 60° or 3 x 60°



SMW-AUTOBLOK Howa Kitagawa Schunk

MAB-M	soft top jaws	16MnCr5	blank w.o. holes	MAB-M blank w.o. holes	 Page 38	MAB-M with holes drilled	 Page 38
MAB-ML	soft top jaws extended versions	16MnCr5	blank w.o. holes				
MAB-M	soft top jaws (Bolt pattern to customer request)	16MnCr5	with holes drilled				
WBJ-M	soft top jaws	16MnCr5	tall	WBJ-M	 Page 39	WBJ-MA Aluminium	 Page 40
WBJ-MA	soft top jaws	aluminium F50	light				
AWB-M	soft top jaws	16MnCr5	tipped	AWB-M tipped	 Page 41		
SBJ-M	soft pie jaws	16MnCr5		SBJ-M	 Page 42	SBJ-MA	 Page 43
SBJ-MA	soft pie jaws	aluminium F50					
WBSA-M	soft top jaws	C45 (flame hardenable)		WBSA-M	 Page 44		

soft top jaws
METRIC serration



safety advise:

Top jaws are safety components, which can enter high load depending on their use.
Max grip forces and speeds must not be exceeded at any time.

For safety reasons all jaws as well as all T-nuts and bolts must be checked for damage and cracks.

smwautoblok@smwautoblok.ru
www.smwautoblok.ru